

**PRODUCT DATA SHEET - COATED FABRICS**

Product Code	PXX200-A61	Rev. No	01
Ref. No	TS/CF-NPD/PDS/154	Date	03.08.15

<i>Product Description</i>	<i>Both side PVC coated fabric - TARPULIN</i>
<i>Finish</i>	<i>Matt</i>
<i>Type of Yarn</i>	<i>High Tenacity Polyester filament yarn</i>
<i>Denier</i>	<i>1000 x 1000 D</i>
<i>Weave</i>	<i>Plain</i>

**Product Properties**

Parameter	Unit	Test Method	Specification	
Product weight	Gsm	IS 7016 Part I - 1982	380	
Thickness	mm	IS 7016 Part I - 1982	0.32	
Breaking Strength	Warp	Kg/5cm	IS 7016 Part II - 1981	230
	Weft	Kg/5cm	IS 7016 Part II - 1981	230
Tear Strength	Warp	Kg	BS: 3424 Part 5 Method 7A	40
	Weft	Kg	BS: 3424 Part 5 Method 7A	40
Adhesion Strength	Kg/5cm	IS 7016 Part V - 1987	3.6	
Water Proofness @ 220 psi	-	IS 7016 Part VII - 1986	No Leak	

**Standard Colors:**

Dark Blue (LW), Federal Blue (LW), Dark Admiral Grey (LW), White (LW).

*Disclaimer: The information contained herein, or that supplied by us, or on our behalf in any manner, is based on data obtained by our own research and is considered accurate. We are submitting it to you to assist you in your endeavors. Values without tolerance statements are values with a **tolerance of ±5%**.*

*This information is subjected to revision as additional technology is developed. SRF Ltd., assumes no liability or obligation for damages incurred through the use of this information and makes no warranty or representation regarding the use of this information.*