

PRODUCT DATA SHEET - COATED FABRICS

Product Code	PPL222-F25	Rev. No	01
Ref. No	TS/CF-NPD/PDS/118	Date	03.08.15

<i>Product Description</i>	<i>Both side PVC coated FR fabric - STRIPE AWNING (DSS)</i>
<i>Finish</i>	<i>Glossy</i>
<i>Surface Treatment</i>	<i>Both side Lacquered</i>
<i>Type of Yarn</i>	<i>High Tenacity Polyester filament yarn</i>
<i>Denier</i>	<i>1000 x 1000 D</i>
<i>Weave</i>	<i>Plain</i>

Product Properties

Parameter	Unit	Test Method	Specification	
Product weight	Gsm	IS 7016 Part I - 1982	580	
Thickness	mm	IS 7016 Part I - 1982	0.47	
Breaking Strength	Warp	Kg/5cm	IS 7016 Part II - 1981	250
	Weft	Kg/5cm	IS 7016 Part II - 1981	240
Tear Strength	Warp	Kg	BS: 3424 Part 5 Method 7A	33
	Weft	Kg	BS: 3424 Part 5 Method 7A	30
Adhesion Strength	Kg/5 cm	IS 7016 Part V - 1987	7.0	
Water Proofness @ 220 psi	-	IS 7016 Part VII - 1986	No Leak	
Fire Retardant	-	DIN 75200	PASS	

Standard Colors:

Stripe Blue, Stripe Green, Yellow-Blue Stripe, Stripe Purple, Yellow-Red Stripe, Stripe Red, Stripe Brown, Stripe Orange.

*Disclaimer: The information contained herein, or that supplied by us, or on our behalf in any manner, is based on data obtained by our own research and is considered accurate. We are submitting it to you to assist you in your endeavors. Values without tolerance statements are values with a **tolerance of ±5%**.*

This information is subjected to revision as additional technology is developed. SRF Ltd., assumes no liability or obligation for damages incurred through the use of this information and makes no warranty or representation regarding the use of this information.